

MX SERIES 2 POLES

Class F insulation - IP55 protection - Voltage test V230-50Hz

TYPE	kW	Hp	rpm	(In) A	Cap. μF	Cap. Start μF	Eff. %	Cos. φ	Ia/In	(Cn) Nm	Ca/Cn	Weight Kg
MX 80 A2	0,75	1	2820	5,6	25	40	68	0,86	5,8	2,54	1,68	10,6
MX 80 B2	1,1	1,5	2800	7,2	30	50	72	0,92	5,4	3,75	1,75	11,2
MX 80 C2	1,5	2	2820	10	30	60	72	0,91	5,6	5,08	1,71	11,9
MX 90S A2	1,5	2	2810	10,5	40	60	73	0,85	5,6	5,10	1,82	14,4
MX 90L A2	1,8	2,5	2830	12,4	50	60	73	0,89	6,0	6,07	1,85	15,4
MX 90L B2	2,2	3	2810	13,5	55	60	78	0,91	5,7	7,48	1,77	15,9
MX 90L C2	2,4	3,3	2790	14,4	60	80	77	0,93	5,5	8,22	1,73	16,4

* = Power not unified - l = Current - a = Start-up - n = Nominal - C = Torque

All technical data can be modified and updated. DAMIEN Electric Motors will can modify them without any notification.